



GUIDE SPECIFICATIONS

WW Series Water-to-Water Reverse Cycle Chillers & Low Temp Boilers

WW120 - 420 Modular Reverse Cycle Chillers/Low Temperature Boilers

GENERAL

Units shall be Underwriter Laboratories (UL) listed for safety on all models. Each unit shall be run tested at the factory. Each unit shall be pallet mounted and stretch wrapped.

The units shall be warranted by the manufacturer against defects in materials and workmanship for a period of one year on all parts, and 5 years on the compressor. The units shall be manufactured in an ISO 9001:2000 certified facility.

The units shall be designed to operate with entering fluid temperatures between 20°F (-7°C) and 120°F (49°C) as manufactured by FHP Manufacturing in Fort Lauderdale, Florida. Refrigerant shall be R-410A.

CASING & CABINET

The cabinet shall be fabricated from heavy-gauge galvanized steel and shall be supported by a full angle iron frame. The interior shall be insulated with ½" (12.7mm) thick, multi density, coated, glass fiber. All units shall allow front service access to replace the compressor and/or electrical components without unit removal.

REFRIGERATION CIRCUITS

All units shall contain a sealed refrigerant circuit including hermetic scroll compressor(s), bidirectional thermal expansion valve metering device(s), coaxial style fluid-to-refrigerant heat exchangers, refrigerant reversing valve(s) and service ports. Compressor shall be high efficiency, designed for heat pump duty with refrigerant R-410A, and mounted on rubber vibration isolators. Compressor motors shall be equipped with overload protection. Refrigerant reversing valves shall be pilot operated sliding piston type with replaceable encapsulated magnetic coils energized only during the chiller cycle. The coaxial water-to-refrigerant heat exchanger shall be constructed of a convoluted copper (optional cupronickel) inner tube and steel outer tube with a designed refrigerant working pressure of 600 PSIG (4100 kPa) and a designed water side working pressure of no less than 400 PSIG (2750 kPa). Due to their

susceptibility to fouling, brazed plate heat exchangers are not acceptable. The fluid-to-refrigerant heat exchangers shall be insulated to prevent condensation at low fluid temperatures.

ELECTRICAL

Controls and safety devices will be factory wired and mounted within the unit. Controls shall include compressor contactors, 24V transformer, reversing valve coils and a solid state lock-out control circuit (UPM). The UPM controller shall include the following features: Anti-short cycle time delay, random start, interstage delay, brown out/surge/power interruption protection, 120 second low pressure switch bypass timer, shutdown on high or low refrigerant pressure safety switch inputs, shutdown for the optional freezestat, 24 VAC alarm output for remote fault indication, unit reset at thermostat or disconnect, ability to defeat time delays for servicing, time delay between stages and automatic intelligent reset. The UPM shall automatically reset after a safety shut down and restart the unit, if the cause of the shut down no longer exists, after the anti-short cycle and random start timers expire. Should a fault re-occur within 60 minutes after reset, then a permanent lockout will occur. A light emitting diode (LED) shall announce the following alarms for each refrigerant circuit: high refrigerant pressure, low refrigerant pressure and low water temperature (when equipped with the optional low water temperature sensor). The LED will display each fault condition as soon as the fault occurs. If a permanent lockout occurs, then the fault LED will display the type of fault until the unit is reset. Safety devices include a low pressure cutout set at 20 PSIG (140 kPa) for loss of charge protection (a freezestat used for loss of charge protection is not acceptable) and a high pressure cutout control set at 600 PSIG (4100 kPa). An optional energy management relay to allow unit control by an external source shall be factory installed.

PIPING

Water piping connections shall be female pipe thread with a single set of source and load connections per unit.



WATER COOLED CHILLERS AND LOW TEMP BOILERS
SPECIFICATION DATA SHEET
 FHP MANUFACTURING ENERGY WISE HVAC EQUIPMENT

WW120
AQUARIUS SERIES
R-410A

ELECTRICAL SPECIFICATIONS

Electrical Characteristics	Elect. Symbol	Compressor		Min. Circuit Ampacity	Max. Fuse Size
		RLA	LRA		
208/230-3-60	-3	37.0	239	46.3	80
460-3-60	-4	20.0	125	25.0	45
575-3-60	-5	14.3	80	17.9	30

FLUID FLOW & PRESSURE DROP

Chilled Fluid Side (@ 55°F)		Cond. Fluid Side (@ 85°F)	
Flow (GPM)	ΔP (FOH)	Flow (GPM)	ΔP (FOH)
18	5.4	18	4.7
22	7.7	22	6.7
26	10.5	26	9.1
30	13.6	30	11.9
34	17.0	34	14.9

UNIT WEIGHT

Unit Weight (lbs) 500
 Shipping Weight (lbs) 520



CHILLER PERFORMANCE

Based on 22.9 GPM load and 28.5 GPM source fluid flow.

Leaving Load Fluid (F)	Entering Source Fluid (F)	Total Capacity (Tons)	Total Capacity (MBtuH)	Power Input (kW)	EER	Heat Rejection (MBtuH)
40°	75°	9.47	113.59	7.13	15.94	137.91
	80°	9.20	110.37	7.50	14.73	135.94
	85°	8.91	106.96	7.91	13.52	133.96
	90°	8.62	103.39	8.38	12.33	131.99
42°	75°	9.79	117.48	7.16	16.41	141.91
	80°	9.52	114.23	7.53	15.18	139.91
	85°	9.23	110.79	7.94	13.95	137.89
	90°	8.93	107.17	8.41	12.74	135.86
44°	75°	9.95	119.46	7.18	16.65	143.94
	80°	9.68	116.20	7.54	15.41	141.93
	85°	9.39	112.74	7.96	14.17	139.89
	90°	9.09	109.09	8.42	12.95	137.83
45°	75°	10.12	121.45	7.19	16.89	145.99
	80°	9.85	118.19	7.56	15.64	143.97
	85°	9.56	114.71	7.97	14.39	141.91
	90°	9.25	111.03	8.44	13.16	139.82
46°	75°	10.46	125.51	7.22	17.37	150.16
	80°	10.19	122.22	7.59	16.10	148.12
	85°	9.89	118.71	8.00	14.83	146.02
	90°	9.58	114.98	8.47	13.58	143.88
48°	75°	10.63	127.57	7.24	17.62	152.28
	80°	10.36	124.27	7.61	16.34	150.23
	85°	10.06	120.74	8.02	15.05	148.11
	90°	9.75	116.99	8.48	13.79	145.93
50°	75°	10.98	131.76	7.27	18.12	156.57
	80°	10.70	128.44	7.64	16.82	154.50
	85°	10.41	124.87	8.05	15.51	152.34
	90°	10.09	121.07	8.52	14.22	150.12
55°	75°	9.75	117.05	9.03	12.97	147.84

HEATING PERFORMANCE

Based on 22.9 GPM load and 28.5 GPM source fluid flow

Leaving Load Fluid (F)	Entering Source Fluid (F)	Heating Capacity (MBtuH)	Power Input (kW)	COP	Heat of Absorb. (MBtuH)
100°	35°	109.52	8.38	3.83	80.94
	40°	117.13	8.36	4.11	88.61
	50°	133.58	8.34	4.69	105.12
	60°	151.63	8.33	5.33	123.19
	70°	171.23	8.33	6.02	142.79
110°	35°	107.57	9.57	3.29	74.91
	40°	114.80	9.53	3.53	82.30
	50°	130.58	9.45	4.05	98.32
	60°	148.09	9.41	4.61	115.99
120°	35°	106.27	10.99	2.83	68.78
	40°	112.97	10.91	3.04	75.75
	50°	127.79	10.78	3.47	91.01
	60°	144.48	10.69	3.96	108.02
125°	35°	105.70	12.62	2.45	62.64
	40°	111.73	12.51	2.62	69.06
	50°	125.31	12.32	2.98	83.28
	60°	140.88	12.17	3.39	99.35
130°	35°	105.70	12.62	2.45	62.64
	40°	111.73	12.51	2.62	69.06
135°	35°	105.70	12.62	2.45	62.64
	40°	111.73	12.51	2.62	69.06

Units are complete packages featuring 1 stage operation and containing refrigeration compressor, reversing valve, expansion valve metering device and water to refrigerant heat exchangers. Also included are safety controls: Overload protection for compressor, high and low refrigerant pressure switches and a lock-out control circuit.

FHP MANUFACTURING COMPANY

601 N.W. 65th Court
 Fort Lauderdale, FL 33309
 Phone: (954) 776-5471 Fax: (800) 776-5529
<http://www.fhp-mfg.com>



WATER COOLED CHILLERS AND LOW TEMP BOILERS
SPECIFICATION DATA SHEET
 FHP MANUFACTURING ENERGY WISE HVAC EQUIPMENT

WW122
AQUARIUS SERIES
R-410A

ELECTRICAL SPECIFICATIONS

Electrical Characteristics	Elect. Symbol	Compressor		Min. Circuit Ampacity	Max. Fuse Size
		RLA	LRA		
208/230-1-60	-1	28.8	169	64.8	80.0
208-230/3/60	-3	19.3	129	43.5	60.0
460/3/60	-4	9.7	75	21.8	30.0

FLUID FLOW & PRESSURE DROP

Chilled Fluid Side (@ 55°F)		Cond. Fluid Side (@ 85°F)	
Flow (GPM)	ΔP (FOH)	Flow (GPM)	ΔP (FOH)
18	5.4	18	4.7
22	7.7	22	6.7
26	10.5	26	9.1
30	13.6	30	11.9
34	17.0	34	14.9

UNIT WEIGHT

Unit Weight (lbs) 520
 Shipping Weight (lbs) 540



CHILLER PERFORMANCE

Based on 23 GPM load and 30 GPM source fluid flow.

Leaving Load Fluid (F)	Entering Source Fluid (F)	Total Capacity (Tons)	Total Capacity (MBtuH)	Power Input (kW)	EER	Heat Rejection (MBtuH)
40°	75°	9.69	116.30	7.31	15.91	141.24
	80°	9.45	113.41	7.78	14.57	139.97
	85°	9.19	110.32	8.29	13.31	138.61
	90°	8.92	107.04	8.84	12.11	137.19
42°	95°	8.63	103.57	9.43	10.99	135.73
	75°	10.05	120.58	7.31	16.51	145.50
	80°	9.80	117.61	7.78	15.12	144.15
	85°	9.54	114.45	8.29	13.81	142.72
44°	90°	9.26	111.09	8.83	12.58	141.22
	95°	8.96	107.54	9.42	11.42	139.67
	75°	10.23	122.76	7.30	16.81	147.68
	80°	9.98	119.76	7.78	15.40	146.29
46°	85°	9.71	116.55	8.28	14.07	144.81
	90°	9.43	113.15	8.83	12.82	143.27
	95°	9.13	109.56	9.41	11.64	141.68
	75°	10.42	124.98	7.30	17.12	149.89
48°	80°	10.16	121.93	7.77	15.69	148.46
	85°	9.89	118.69	8.28	14.34	146.94
	90°	9.60	115.25	8.82	13.06	145.35
	95°	9.30	111.61	9.41	11.86	143.72
50°	75°	10.79	129.52	7.30	17.75	154.41
	80°	10.53	126.38	7.77	16.27	152.88
	85°	10.25	123.05	8.27	14.88	151.28
	90°	9.96	119.52	8.82	13.56	149.60
52°	95°	9.65	115.80	9.40	12.32	147.88
	75°	10.99	131.83	7.29	18.07	156.72
	80°	10.72	128.66	7.76	16.57	155.15
	85°	10.44	125.28	8.27	15.15	153.49
54°	90°	10.14	121.71	8.81	13.81	151.77
	95°	9.83	117.93	9.40	12.55	150.00
	75°	11.38	136.58	7.29	18.74	161.45
	80°	11.11	133.31	7.76	17.19	159.77
56°	85°	10.82	129.84	8.26	15.72	158.02
	90°	10.51	126.17	8.80	14.33	156.20
	95°	10.19	122.30	9.39	13.03	154.32

HEATING PERFORMANCE

Based on 23 GPM load and 30 GPM source fluid flow

Leaving Load Fluid (F)	Entering Source Fluid (F)	Heating Capacity (MBtuH)	Power Input (kW)	COP	Heat of Absorb. (MBtuH)
100°	35°	114.15	9.01	3.71	83.41
	40°	121.91	8.93	4.00	91.44
	50°	138.67	8.76	4.64	108.78
	60°	157.33	8.57	5.38	128.09
	70°	178.19	8.36	6.25	149.69
110°	35°	112.67	10.28	3.21	77.61
	40°	120.25	10.19	3.46	85.49
	50°	136.55	9.99	4.00	102.46
	60°	154.62	9.77	4.64	121.28
120°	70°	174.78	9.53	5.38	142.27
	35°	111.19	11.75	2.77	71.09
	40°	118.58	11.66	2.98	78.81
	50°	134.38	11.44	3.44	95.36
130°	60°	151.83	11.19	3.98	113.65
	70°	171.24	10.91	4.60	134.00
	35°	109.85	13.48	2.39	63.84
	40°	117.02	13.37	2.56	71.38
140°	50°	132.28	13.13	2.95	87.47
	60°	149.07	12.86	3.40	105.19
	70°	167.69	12.55	3.92	124.86

Units are complete packages featuring 1 stage operation and containing refrigeration compressor, reversing valve, expansion valve metering device and water to refrigerant heat exchangers. Also included are safety controls: Overload protection for compressor, high and low refrigerant pressure switches and a lock-out control circuit.

FHP MANUFACTURING COMPANY

601 N.W. 65th Court
 Fort Lauderdale, FL 33309
 Phone: (954) 776-5471 Fax: (800) 776-5529
<http://www.fhp-mfg.com>



WATER COOLED CHILLERS AND LOW TEMP BOILERS
SPECIFICATION DATA SHEET
 FHP MANUFACTURING ENERGY WISE HVAC EQUIPMENT

WW180
AQUARIUS SERIES
R-410A

ELECTRICAL SPECIFICATIONS

Electrical Characteristics	Elect. Symbol	Compressor		Min. Circuit Ampacity	Max. Fuse Size
		RLA	LRA		
208/230-3-60	-3	53.6	245	67.0	120
460-3-60	-4	20.7	125	25.9	40
575-3-60	-5	16.4	100	20.5	35

FLUID FLOW & PRESSURE DROP

Chilled Fluid Side (@ 55°F)		Cond. Fluid Side (@ 85°F)	
Flow (GPM)	ΔP (FOH)	Flow (GPM)	ΔP (FOH)
22	4.6	22	4.0
26	6.2	26	5.4
30	8.1	30	7.0
34	10.1	34	8.8
38	12.4	38	10.8

UNIT WEIGHT

Unit Weight (lbs) 740
 Shipping Weight (lbs) 760



CHILLER PERFORMANCE

Based on 25.9 GPM load and 32.2 GPM source fluid flow.

Leaving Load Fluid (F)	Entering Source Fluid (F)	Total Capacity (Tons)	Total Capacity (MBtuH)	Power Input (kW)	EER	Heat Rejection (MBtuH)
40°	75°	10.7	128.90	7.95	16.22	156.02
	80°	10.5	125.49	8.40	14.93	154.17
	85°	10.2	122.01	8.89	13.72	152.36
	90°	9.9	118.45	9.42	12.58	150.58
	95°	9.6	114.77	9.98	11.50	148.83
42°	75°	11.1	133.06	7.99	16.66	160.31
	80°	10.8	129.55	8.44	15.35	158.35
	85°	10.5	125.97	8.93	14.11	156.44
	90°	10.2	122.31	9.45	12.94	154.57
	95°	9.9	118.54	10.02	11.84	152.71
44°	75°	11.3	135.18	8.00	16.89	162.49
	80°	11.0	131.62	8.46	15.56	160.48
	85°	10.7	127.99	8.95	14.30	158.52
	90°	10.4	124.28	9.47	13.12	156.59
	95°	10.0	120.46	10.03	12.01	154.69
45°	75°	11.4	137.33	8.02	17.12	164.71
	80°	11.1	133.71	8.48	15.77	162.64
	85°	10.8	130.03	8.97	14.50	160.63
	90°	10.5	126.27	9.49	13.31	158.65
	95°	10.2	122.40	10.05	12.18	156.69
46°	75°	11.8	141.71	8.06	17.57	169.22
	80°	11.5	137.98	8.52	16.20	167.04
	85°	11.2	134.19	9.00	14.90	164.91
	90°	10.9	130.32	9.53	13.68	162.82
	95°	10.5	126.34	10.09	12.53	160.76
48°	75°	12.0	143.94	8.08	17.81	171.52
	80°	11.7	140.15	8.54	16.42	169.28
	85°	11.4	136.30	9.02	15.10	167.09
	90°	11.0	132.38	9.55	13.87	164.95
	95°	10.7	128.35	10.11	12.70	162.83
50°	75°	12.4	148.48	8.13	18.27	176.20
	80°	12.0	144.57	8.58	16.85	173.84
	85°	11.7	140.61	9.06	15.51	171.53
	90°	11.4	136.57	9.59	14.25	169.27
	95°	11.0	132.43	10.14	13.06	167.04

HEATING PERFORMANCE

Based on 25.9 GPM load and 32.2 GPM source fluid flow

Leaving Load Fluid (F)	Entering Source Fluid (F)	Heating Capacity (MBtuH)	Power Input (kW)	COP	Heat of Absorb. (MBtuH)
100°	35°	127.17	9.35	3.99	95.27
	40°	135.05	9.35	4.23	103.14
	50°	152.05	9.37	4.76	120.09
	60°	170.86	9.39	5.33	138.82
	70°	191.67	9.43	5.96	159.51
110°	35°	125.33	10.57	3.48	89.28
	40°	132.95	10.56	3.69	96.92
	50°	149.32	10.55	4.15	113.31
	60°	167.35	10.56	4.65	131.34
	70°	187.25	10.57	5.19	151.18
120°	35°	123.45	11.96	3.03	82.65
	40°	130.82	11.94	3.21	90.08
	50°	146.59	11.91	3.61	105.95
	60°	163.89	11.89	4.04	123.31
	70°	182.90	11.89	4.51	142.33
125°	35°	121.46	13.55	2.63	75.24
	40°	128.61	13.52	2.79	82.49
	50°	143.81	13.46	3.13	97.87
	60°	160.39	13.42	3.50	114.59
	70°	178.54	13.40	3.91	132.84

Units are complete packages featuring 1 stage operation and containing refrigeration compressor, reversing valve, expansion valve metering device and water to refrigerant heat exchangers. Also included are safety controls: Overload protection for compressor, high and low refrigerant pressure switches and a lock-out control circuit.

FHP MANUFACTURING COMPANY

601 N.W. 65th Court
 Fort Lauderdale, FL 33309
 Phone: (954) 776-5471 Fax: (800) 776-5529
<http://www.fhp-mfg.com>



WATER COOLED CHILLERS AND LOW TEMP BOILERS
SPECIFICATION DATA SHEET
 FHP MANUFACTURING ENERGY WISE HVAC EQUIPMENT

WW210
AQUARIUS SERIES
R-410A

ELECTRICAL SPECIFICATIONS

Electrical Characteristics	Elect. Symbol	Compressor		Min. Circuit Ampacity	Max. Fuse Size
		RLA	LRA		
208/230-3-60	-3	59.1	425	73.9	130
460-3-60	-4	26.4	187	33.0	50
575-3-60	-5	26.0	148	32.5	50

FLUID FLOW & PRESSURE DROP

Chilled Fluid Side (@ 55°F)		Cond. Fluid Side (@ 85°F)	
Flow (GPM)	ΔP (FOH)	Flow (GPM)	ΔP (FOH)
25	5.8	25	5.0
30	8.0	30	7.0
35	10.6	35	9.3
40	13.5	40	11.8
45	16.8	45	14.7

UNIT WEIGHT

Unit Weight (lbs) 770
 Shipping Weight (lbs) 790



CHILLER PERFORMANCE

Based on 34.0 GPM load & 42.1 GPM source fluid flow.

Leaving Load Fluid (F)	Entering Source Fluid (F)	Total Capacity (Tons)	Total Capacity (MBtuH)	Power Input (kW)	EER	Heat Rejection (MBtuH)
40°	75°	13.97	167.70	10.73	15.63	204.31
	80°	13.59	163.12	11.30	14.43	201.69
	85°	13.20	158.45	11.94	13.27	199.18
	90°	12.81	153.69	12.63	12.17	196.77
42°	95°	12.40	148.84	13.37	11.13	194.46
	75°	14.48	173.80	10.79	16.11	210.62
	80°	14.09	169.06	11.36	14.89	207.81
	85°	13.69	164.24	11.99	13.70	205.13
44°	90°	13.28	159.31	12.67	12.57	202.55
	95°	12.86	154.29	13.41	11.50	200.06
	75°	14.74	176.92	10.82	16.35	213.84
	80°	14.34	172.10	11.39	15.12	210.95
45°	85°	13.93	167.19	12.01	13.92	208.17
	90°	13.52	162.19	12.69	12.78	205.50
	95°	13.09	157.08	13.44	11.69	202.92
	46°	75°	15.01	180.09	10.85	16.59
80°		14.60	175.18	11.41	15.35	214.13
85°		14.18	170.19	12.04	14.14	211.26
90°		13.76	165.10	12.72	12.98	208.49
48°	95°	13.33	159.91	13.46	11.88	205.83
	75°	15.55	186.55	10.93	17.07	223.83
	80°	15.12	181.48	11.48	15.81	220.65
	85°	14.69	176.32	12.09	14.58	217.58
50°	90°	14.25	171.05	12.77	13.40	214.62
	95°	13.81	165.68	13.51	12.27	211.76
	75°	15.82	189.85	10.97	17.31	227.27
	80°	15.39	184.70	11.51	16.04	223.98
50°	85°	14.95	179.44	12.12	14.80	220.81
	90°	14.51	174.09	12.80	13.61	217.75
	95°	14.05	168.63	13.53	12.46	214.79
	75°	16.38	196.60	11.05	17.80	234.29
50°	80°	15.94	191.27	11.58	16.51	230.79
	85°	15.49	185.83	12.19	15.25	227.41
	90°	15.02	180.30	12.85	14.03	224.15
	95°	14.55	174.65	13.58	12.86	221.00

HEATING PERFORMANCE

Based on 34.0 GPM load and 42.1 GPM source fluid flow

Leaving Load Fluid (F)	Entering Source Fluid (F)	Heating Capacity (MBtuH)	Power Input (kW)	COP	Heat of Absorb. (MBtuH)
100°	35°	164.07	12.59	3.82	121.10
	40°	175.01	12.58	4.08	132.09
	50°	199.05	12.56	4.64	156.19
	60°	226.30	12.58	5.27	183.36
	70°	257.17	12.70	5.94	213.84
110°	35°	162.19	14.16	3.36	113.89
	40°	172.66	14.16	3.57	124.36
	50°	195.56	14.13	4.06	147.35
	60°	221.45	14.11	4.60	173.31
120°	70°	250.73	14.14	5.20	202.48
	35°	160.51	15.89	2.96	106.29
	40°	170.51	15.92	3.14	116.20
	50°	192.32	15.92	3.54	138.00
125°	60°	216.87	15.89	4.00	162.66
	70°	244.60	15.88	4.52	190.43
	35°	158.93	17.79	2.62	98.24
	40°	168.49	17.86	2.77	107.56
125°	50°	189.23	17.92	3.09	128.08
	60°	212.49	17.92	3.48	151.36
	70°	238.69	17.89	3.91	177.65

Units are complete packages featuring 1 stage operation and containing refrigeration compressor, reversing valve, expansion valve metering device and water to refrigerant heat exchangers. Also included are safety controls: Overload protection for compressor, high and low refrigerant pressure switches and a lock-out control circuit.

FHP MANUFACTURING COMPANY

601 N.W. 65th Court
 Fort Lauderdale, FL 33309
 Phone: (954) 776-5471 Fax: (800) 776-5529
<http://www.fhp-mfg.com>



WATER COOLED CHILLERS AND LOW TEMP BOILERS
SPECIFICATION DATA SHEET
 FHP MANUFACTURING ENERGY WISE HVAC EQUIPMENT

WW240
AQUARIUS SERIES
R-410A

ELECTRICAL SPECIFICATIONS

Electrical Characteristics	Elect. Symbol	Compressor		Min. Circuit Ampacity	Max. Fuse Size
		RLA	LRA		
208/230-3-60	-3	37.0	239	83.3	120
460-3-60	-4	20.0	125	45.0	60
575-3-60	-5	14.3	80	32.2	45

FLUID FLOW & PRESSURE DROP

Chilled Fluid Side (@ 55°F)		Cond. Fluid Side (@ 85°F)	
Flow (GPM)	ΔP (FOH)	Flow (GPM)	ΔP (FOH)
36	5.4	36	4.7
44	7.7	44	6.7
52	10.5	52	9.1
60	13.6	60	11.9
68	17.0	68	14.9

UNIT WEIGHT

Unit Weight (lbs) 970
 Shipping Weight (lbs) 990



CHILLER PERFORMANCE

Based on 45.8 GPM load and 57 GPM source fluid flow.

Leaving Load Fluid (F)	Entering Source Fluid (F)	Total Capacity (Tons)	Total Capacity (MBtuH)	Power Input (kW)	EER	Heat Rejection (MBtuH)
40°	75°	18.93	227.18	14.26	15.94	275.83
	80°	18.39	220.73	14.99	14.73	271.88
	85°	17.83	213.92	15.83	13.52	267.92
	90°	17.23	206.78	16.76	12.33	263.98
	95°	16.61	199.34	17.80	11.20	260.09
42°	75°	19.58	234.96	14.32	16.41	283.82
	80°	19.04	228.47	15.05	15.18	279.83
	85°	18.47	221.58	15.89	13.95	275.78
	90°	17.86	214.34	16.82	12.74	271.72
	95°	17.23	206.77	17.86	11.58	267.69
44°	75°	19.91	238.91	14.35	16.65	287.88
	80°	19.37	232.40	15.08	15.41	283.87
	85°	18.79	225.48	15.92	14.17	279.78
	90°	18.18	218.18	16.85	12.95	275.67
	95°	17.55	210.54	17.88	11.77	271.56
45°	75°	20.24	242.91	14.38	16.89	291.99
	80°	19.70	236.37	15.12	15.64	287.95
	85°	19.12	229.41	15.95	14.39	283.82
	90°	18.51	222.06	16.88	13.16	279.65
	95°	17.86	214.36	17.91	11.97	275.47
46°	75°	20.92	251.02	14.45	17.37	300.32
	80°	20.37	244.45	15.18	16.10	296.24
	85°	19.78	237.41	16.01	14.83	292.04
	90°	19.16	229.96	16.94	13.58	287.75
	95°	18.51	222.12	17.96	12.36	283.42
48°	75°	21.26	255.14	14.48	17.62	304.55
	80°	20.71	248.55	15.21	16.34	300.45
	85°	20.12	241.48	16.04	15.05	296.21
	90°	19.50	233.97	16.97	13.79	291.87
	95°	18.84	226.07	17.99	12.56	287.46
50°	75°	21.96	263.52	14.54	18.12	313.14
	80°	21.41	256.88	15.28	16.82	309.00
	85°	20.81	249.74	16.10	15.51	304.69
	90°	20.18	242.13	17.03	14.22	300.24
	95°	19.51	234.09	18.05	12.97	295.69

HEATING PERFORMANCE

Based on 45.8GPM load and 57 GPM source fluid flow

Leaving Load Fluid (F)	Entering Source Fluid (F)	Heating Capacity (MBtuH)	Power Input (kW)	COP	Heat of Absorb. (MBtuH)
100°	35°	219.05	16.75	3.83	161.89
	40°	234.27	16.72	4.11	177.22
	50°	267.16	16.68	4.69	210.25
	60°	303.25	16.67	5.33	246.38
	70°	342.45	16.67	6.02	285.58
110°	35°	215.15	19.14	3.29	149.83
	40°	229.61	19.05	3.53	164.60
	50°	261.16	18.91	4.05	196.64
	60°	296.18	18.82	4.61	231.99
	70°	334.59	18.76	5.23	270.60
120°	35°	212.54	21.98	2.83	137.56
	40°	225.95	21.82	3.04	151.51
	50°	255.59	21.56	3.47	182.02
	60°	288.96	21.37	3.96	216.03
	70°	326.00	21.24	4.50	253.52
125°	35°	211.40	25.24	2.45	125.27
	40°	223.47	25.02	2.62	138.12
	50°	250.62	24.63	2.98	166.57
	60°	281.77	24.35	3.39	198.70
	70°	316.85	24.13	3.85	234.51

Units are complete packages featuring 1 stage operation and containing refrigeration compressor, reversing valve, expansion valve metering device and water to refrigerant heat exchangers. Also included are safety controls: Overload protection for compressor, high and low refrigerant pressure switches and a lock-out control circuit.

FHP MANUFACTURING COMPANY

601 N.W. 65th Court
 Fort Lauderdale, FL 33309
 Phone: (954) 776-5471 Fax: (800) 776-5529
<http://www.fhp-mfg.com>



WATER COOLED CHILLERS AND LOW TEMP BOILERS
SPECIFICATION DATA SHEET
 FHP MANUFACTURING ENERGY WISE HVAC EQUIPMENT

WW360
AQUARIUS SERIES
R-410A

ELECTRICAL SPECIFICATIONS

Electrical Characteristics	Elect. Symbol	Compressor		Min. Circuit Ampacity	Max. Fuse Size
		RLA	LRA		
208/230-3-60	-3	53.6	245	120.6	170
460-3-60	-4	20.7	125	46.6	60
575-3-60	-5	16.4	100	36.9	50

FLUID FLOW & PRESSURE DROP

Chilled Fluid Side (@ 55°F)		Cond. Fluid Side (@ 85°F)	
Flow (GPM)	ΔP (FOH)	Flow (GPM)	ΔP (FOH)
44	4.6	44	4.0
52	6.2	52	5.4
60	8.1	60	7.0
68	10.1	68	8.8
76	12.4	76	10.8

UNIT WEIGHT

Unit Weight (lbs) 970
 Shipping Weight (lbs) 990



CHILLER PERFORMANCE

Based on 51.8 GPM load & 64.4 GPM source fluid flow.

Leaving Load Fluid (F)	Entering Source Fluid (F)	Total Capacity (Tons)	Total Capacity (MBtuH)	Power Input (kW)	EER	Heat Rejection (MBtuH)
40°	75°	21.48	257.79	15.90	16.22	312.03
	80°	20.92	250.98	16.81	14.93	308.33
	85°	20.34	244.02	17.79	13.72	304.72
	90°	19.74	236.89	18.84	12.58	301.16
42°	95°	19.13	229.54	19.96	11.50	297.66
	75°	22.18	266.12	15.97	16.66	320.61
	80°	21.59	259.10	16.88	15.35	316.71
	85°	21.00	251.95	17.86	14.11	312.88
44°	90°	20.39	244.62	18.91	12.94	309.13
	95°	19.76	237.09	20.03	11.84	305.43
	75°	22.53	270.36	16.01	16.89	324.99
	80°	21.94	263.24	16.92	15.56	320.97
45°	85°	21.33	255.98	17.90	14.30	317.04
	90°	20.71	248.55	18.94	13.12	313.19
	95°	20.08	240.92	20.07	12.01	309.38
	46°	75°	22.89	274.66	16.05	17.12
80°		22.29	267.43	16.96	15.77	325.29
85°		21.67	260.06	17.93	14.50	321.25
90°		21.04	252.53	18.98	13.31	317.29
48°	95°	20.40	244.80	20.10	12.18	313.38
	75°	23.62	283.41	16.13	17.57	338.44
	80°	23.00	275.96	17.03	16.20	334.08
	85°	22.36	268.38	18.01	14.90	329.82
50°	90°	21.72	260.63	19.05	13.68	325.64
	95°	21.06	252.69	20.17	12.53	321.52
	75°	23.99	287.87	16.17	17.81	343.03
	80°	23.36	280.30	17.07	16.42	338.56
52°	85°	22.72	272.60	18.05	15.10	334.18
	90°	22.06	264.75	19.09	13.87	329.89
	95°	21.39	256.70	20.21	12.70	325.66
	54°	75°	24.75	296.95	16.25	18.27
80°		24.10	289.14	17.16	16.85	347.68
85°		23.43	281.22	18.13	15.51	343.07
90°		22.76	273.13	19.17	14.25	338.54
56°	95°	22.07	264.86	20.29	13.06	334.08

HEATING PERFORMANCE

Based on 51.8 GPM load and 64.4 GPM source fluid flow

Leaving Load Fluid (F)	Entering Source Fluid (F)	Heating Capacity (MBtuH)	Power Input (kW)	COP	Heat of Absorb. (MBtuH)
100°	35°	254.35	18.70	3.99	190.55
	40°	270.10	18.71	4.23	206.28
	50°	304.10	18.73	4.76	240.18
	60°	341.71	18.78	5.33	277.64
	70°	383.34	18.85	5.96	319.01
110°	35°	250.66	21.13	3.48	178.56
	40°	265.90	21.12	3.69	193.85
	50°	298.63	21.10	4.15	226.63
	60°	334.71	21.11	4.65	262.68
120°	70°	374.50	21.15	5.19	302.35
	35°	246.90	23.92	3.03	165.30
	40°	261.65	23.88	3.21	180.17
	50°	293.19	23.82	3.61	211.90
125°	60°	327.77	23.79	4.04	246.61
	70°	365.80	23.78	4.51	284.67
	35°	242.92	27.09	2.63	150.49
	40°	257.21	27.03	2.79	164.98
130°	50°	287.61	26.93	3.13	195.74
	60°	320.77	26.85	3.50	229.17
	70°	357.09	26.79	3.91	265.67

Units are complete packages featuring 1 stage operation and containing refrigeration compressor, reversing valve, expansion valve metering device and water to refrigerant heat exchangers. Also included are safety controls: Overload protection for compressor, high and low refrigerant pressure switches and a lock-out control circuit.

FHP MANUFACTURING COMPANY

601 N.W. 65th Court
 Fort Lauderdale, FL 33309
 Phone: (954) 776-5471 Fax: (800) 776-5529
<http://www.fhp-mfg.com>



WATER COOLED CHILLERS AND LOW TEMP BOILERS
SPECIFICATION DATA SHEET
 FHP MANUFACTURING ENERGY WISE HVAC EQUIPMENT

WW420
AQUARIUS SERIES
R-410A

ELECTRICAL SPECIFICATIONS

Electrical Characteristics	Elect. Symbol	Compressor		Min. Circuit Ampacity	Max. Fuse Size
		RLA	LRA		
208/230-3-60	-3	59.1	425	133.0	190
460-3-60	-4	26.4	187	59.4	80
575-3-60	-5	26	148	58.5	80

FLUID FLOW & PRESSURE DROP

Chilled Fluid Side (@ 55°F)		Cond. Fluid Side (@ 85°F)	
Flow (GPM)	ΔP (FOH)	Flow (GPM)	ΔP (FOH)
50	5.8	50	5.0
60	8.0	60	7.0
70	10.6	70	9.3
80	13.5	80	11.8
90	16.8	90	14.7

UNIT WEIGHT

Unit Weight (lbs) 1550
 Shipping Weight (lbs) 1570



CHILLER PERFORMANCE

Based on 68 GPM load and 84.2 GPM source fluid flow.

Leaving Load Fluid (F)	Entering Source Fluid (F)	Total Capacity (Tons)	Total Capacity (MBtuH)	Power Input (kW)	EER	Heat Rejection (MBtuH)
40°	75°	27.95	335.40	21.46	15.63	408.61
	80°	27.19	326.23	22.61	14.43	403.37
	85°	26.41	316.89	23.88	13.27	398.36
	90°	25.61	307.38	25.26	12.17	393.55
	95°	24.81	297.67	26.74	11.13	388.92
42°	75°	28.97	347.61	21.58	16.11	421.23
	80°	28.18	338.13	22.71	14.89	415.63
	85°	27.37	328.47	23.97	13.70	410.26
	90°	26.55	318.63	25.34	12.57	405.09
	95°	25.72	308.59	26.83	11.50	400.12
44°	75°	29.49	353.85	21.64	16.35	427.69
	80°	28.68	344.21	22.77	15.12	421.90
	85°	27.87	334.38	24.02	13.92	416.34
	90°	27.03	324.37	25.39	12.78	411.00
	95°	26.18	314.16	26.87	11.69	405.84
45°	75°	30.01	360.17	21.71	16.59	434.25
	80°	29.20	350.37	22.83	15.35	428.27
	85°	28.37	340.38	24.07	14.14	422.52
	90°	27.52	330.20	25.44	12.98	416.99
	95°	26.65	319.81	26.92	11.88	411.65
46°	75°	31.09	373.10	21.85	17.07	447.67
	80°	30.25	362.96	22.96	15.81	441.29
	85°	29.39	352.63	24.19	14.58	435.15
	90°	28.51	342.10	25.54	13.40	429.24
	95°	27.61	331.36	27.01	12.27	423.52
48°	75°	31.64	379.71	21.93	17.31	454.53
	80°	30.78	369.39	23.02	16.04	447.95
	85°	29.91	358.89	24.25	14.80	441.6
	90°	29.01	348.18	25.59	13.61	435.50
	95°	28.10	337.26	27.06	12.46	429.59
50°	75°	32.77	393.19	22.10	17.80	468.58
	80°	31.88	382.53	23.17	16.51	461.58
	85°	30.97	371.67	24.37	15.25	454.83
	90°	30.05	360.59	25.71	14.03	448.30
	95°	29.11	349.30	27.17	12.86	441.99

HEATING PERFORMANCE

Based on 68 GPM load and 84.2 GPM source fluid flow

Leaving Load Fluid (F)	Entering Source Fluid (F)	Heating Capacity (MBtuH)	Power Input (kW)	COP	Heat of Absorb. (MBtuH)
100°	35°	328.13	25.18	3.82	242.21
	40°	350.02	25.16	4.08	264.18
	50°	398.09	25.12	4.64	312.39
	60°	452.59	25.17	5.27	366.72
	70°	514.34	25.40	5.94	427.69
110°	35°	324.39	28.31	3.36	227.78
	40°	345.32	28.31	3.57	248.72
	50°	391.12	28.26	4.06	294.71
	60°	442.89	28.22	4.60	346.61
	70°	501.46	28.28	5.20	404.95
120°	35°	321.01	31.78	2.96	212.58
	40°	341.02	31.83	3.14	232.41
	50°	384.63	31.84	3.54	276.01
	60°	433.74	31.78	4.00	325.32
	70°	489.20	31.75	4.52	380.86
125°	35°	317.86	35.57	2.62	196.48
	40°	336.98	35.72	2.77	215.12
	50°	378.46	35.84	3.09	256.17
	60°	424.98	35.83	3.48	302.71
	70°	477.39	35.78	3.91	355.30

Units are complete packages featuring 1 stage operation and containing refrigeration compressor, reversing valve, expansion valve metering device and water to refrigerant heat exchangers. Also included are safety controls: Overload protection for compressor, high and low refrigerant pressure switches and a lock-out control circuit.

FHP MANUFACTURING COMPANY

601 N.W. 65th Court
 Fort Lauderdale, FL 33309
 Phone: (954) 776-5471 Fax: (800) 776-5529
<http://www.fhp-mfg.com>